



Screen all who enter with a SpeedFace+ reader.

Guard your school entrances with SpeedFace+. These high-performance face, palm, and fingerprint recognition readers verify that everyone who wants to enter has an appropriate body temperature and is wearing a protective mask. Use it solo, or at multiple points of entry when teamed with the all-in-one ZKBioSecurity* web-based remote security platform. Full support is also available* to help ensure proper setup and resolve any questions, for security you can count on.

*Sold separately.

Secure. Accurate. Affordable.

- Authenticates from up to 8 feet away
- Reads body temperature within +/- 0.6°F from up to 18 inches*. SF1008T+ reads up to 2.5 feet*
- Face verification possible while wearing mask (palm recognition advised)
- Thermal imaging camera included for SF1008T+
- Add fingerprint recognition by choosing model SF1005-V+
- Works in any lighting from total darkness to bright sun
- Desktop or wall mount available
- Calibration not needed for Model SF1008 T+; adapts to unstable environments

Capacity

Model SF1008+ and SF1008 T+:

Faces: 50,000 | Palms: 5,000

Model SF1005-V+:

Faces: 6,000 | Palms: 3,000 | Fingerprints: 10,000

Measuring Points

Models SF1008+ and SF1005-V+: 1,024

Model SF1008 T+: 10,800

Compatibility

Wiegand Input Panels

Wiegand Output readers

ZKBioSecurity Software

ZKTeco Security Relay Box (SRB)

Hardware

900 MHz Dual Core CPU

512MB RAM / 8 GB Flash

8" or 5" Touch Screen Display (8" only on SF1008T+)

2MP WDR Camera

Distance Detection Sensor

Reset Button & Tamper Switch

Access Control Interface

Lock Relay Output

Alarm Output / Auxiliary Input Exit

Button / Door Sensor

Special Functions

0.3s Recognition Speed

Liveness Detection

Event Snapshot

Standard Functions

Access Levels, Groups, Holidays

DST, Duress Mode (password)

Anti-Passback, Record Query

Tamper Switch Alarm

Communication

TCP/IP

RS485

Wiegand Input / Output

Optional Wi-Fi

Size

Models SF1008+ and SF1008-T+: 8.9" x 5.6" x 1"

Model SF-1005-V+: 8" x 3.6" x 1"

Additional Info

Face Algorithm: ZKLiveFace 5.8

Working Temp: -22° to 140°F

Model SF1008-T+ Working Temp: -40 to 140 F

Working Humidity: ≤93%

Storage Temp: -40° to 169°F

Model SF1008-T+ Storage Temp: 31 to 122 F

Storage Humidity: ≤93%

Model SF1008-T+ Storage and Working Humidity: 20%–90%

Net Weight: 1.5 lbs.

Power

Operating Voltage: 12V DC

Current Draw: <2,000mA

Temperature Detection

Accuracy: +/- 0.6 ° F

Model SF1008+ and SF1005-V+ Distance: Up to 18 inches

Model SF1008T+ Distance: Up to 2.5 feet

*Temperature specification in climate controlled rooms. All specifications subject to change without notice. All other product and company names mentioned are used for identification purposes only and may be trademarks of their respective owners. This device is not approved by the FDA as a medical use thermometer.

Questions? Contact your School Specialty Sales Representative today.